# Safety Data Sheet



**Revision Number: 001.5** Issue date: 06/07/2021

# PRODUCT AND COMPANY IDENTIFICATION

Product name: **GE Painter's Pro Seal And Paint** 

Product type/use: Sealant None identified **Restriction of Use:** 

Henkel Corporation

One Henkel Way

Company address:

Rocky Hill, Connecticut 06067

IDH number: 2874546

Region: **United States** 

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

# **EMERGENCY OVERVIEW**

NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

	HAZARD CLASS	HAZARD CATEGORY
None		None

#### PICTOGRAM(S) None

#### **Precautionary Statements**

Prevention: Not prescribed Response: Not prescribed Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### **COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Wash affected area immediately with soap and water. If symptoms develop

and persist, get medical attention.

If irritation develops, flush eyes immediately with large amounts of water. If Eye contact:

irritation persists, seek medical attention or advice.

Rinse out mouth. Do not drink. Never give anything by mouth to an Ingestion:

unconscious person. If adverse health effects develop seek medical attention.

See Section 11. Symptoms:

IDH number: 2874546 Product name: GE Painter's Pro Seal And Paint

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Water may be unsuitable as an extinguishing media, but may be helpful in

keeping adjacent containers cool.

Unusual fire or explosion hazards: Closed containers may explode when exposed to extreme heat.

Hazardous combustion products: Oxides of nitrogen. Oxides of carbon.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not let product enter drains.

Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for disposal. Wear appropriate protective equipment and clothing during clean-up.

# 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes. Avoid prolonged or repeated skin contact with this

material. Keep out of the reach of children.

Storage: Keep from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

#### **EXPOSURE CONTROLS / PERSONAL PROTECTION**

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

**Engineering controls:** Use local exhaust ventilation.

Respiratory protection: No personal respiratory protective equipment normally required.

Eye/face protection: None required in normal use.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

### PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Clear Odor: Acrylic Odor threshold: Not available. :Ha 7.7 - 8.6

15 mm hg (20 °C (68°F)) Vapor pressure:

Boiling point/range: 100 °C (212°F) Melting point/ range: Specific gravity: Not available.

1.06

Heavier than air, (Air = 1) Vapor density:

Flash point: > 93.3 °C (> 199.94 °F) Pensky Martens closed cup

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable Evaporation rate: 0.5 (Butyl acetate = 1)

Solubility in water: Soluble Partition coefficient (n-octanol/water): Not available.

1 %; < 15 g/l (by weight, calculated using CARB method; g/L less water, less VOC content:

exempts calculated using SCAQMD method)

IDH number: 2874546 Product name: GE Painter's Pro Seal And Paint Viscosity: 250,000 - 350,000 cp Decomposition temperature: Not available.

#### 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Oxides of carbon. Oxides of nitrogen.

**Incompatible materials:** This product may react with strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

#### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin

#### **Potential Health Effects/Symptoms**

Inhalation: Inhalation of vapors from uncured sealant may cause respiratory tract irritation.

Skin contact: Prolonged or repeated contact with this product may dry and/or defat the skin.

**Eye contact:** Contact with uncured product may irritate the eyes.

Ingestion: Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal

irritation and disturbances.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
None	None	None

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	None	None

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

IDH number: 2874546 Product name: GE Painter's Pro Seal And Paint

#### Water Transportation (IMO/IMDG)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: None

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: Reviewed SDS. Reissued with new date.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/07/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 2874546 Product name: GE Painter's Pro Seal And Paint